

This call returns the address of a global and local information segment, specific to a process.

Syntax

DosGetInfoSeg (GlobalSeg, LocalSeg)

Parameters

;GlobalSeg (PSEL) - output : Address of the global information segment structure, as defined below:
:time (ULONG): Time in seconds since 1/1/1970. :millisecs (ULONG): Time in milliseconds. :hours
(UCHAR): Current hour. :minute (UCHAR): Current minute. :seconds (UCHAR): Current second.
:hundredsec (UCHAR): Current hundredth of a second. :timezone (USHORT): Minutes from UTC; if hex
FFFFH, timezone is undefined. :interval (USHORT): Timer interval in tenths of milliseconds. :day
(UCHAR): Day. :month (UCHAR): Month. :year (USHORT): Year. :weekday (UCHAR): Day-of-week:
Value Definition 0 Sunday 1 Monday 2 Tuesday 3 Wednesday 4 Thursday 5 Friday 6 Saturday
:majorversion (UCHAR): Major version number. :minorversion (UCHAR): Minor version number.
:revision (UCHAR): Revision letter. :currentsession (UCHAR): Current foreground full-screen session.
:maxnumsessions (UCHAR): Maximum number of full-screen sessions. :hugeshift (UCHAR): Shift count
for huge segments. :protmodeind (UCHAR): Protect-mode-only indicator: Value Definition 0 DOS mode
and OS/2 mode. 1 OS/2 mode only. :lastprocess (USHORT) : Process ID of the current foreground
process. :dynvarflag (UCHAR) : Dynamic variation flag: Value Definition 0 Absolute 1 Enabled.
:maxwait (UCHAR) : Maximum wait in seconds. :mintimeslice (USHORT) : Minimum timeslice in
milliseconds. :maxtimeslice (USHORT) : Maximum timeslice in milliseconds. :bootdrive (USHORT) :
Drive from which the system was booted: Value Definition 1 Drive A. 2 Drive B. . . . n Drive n.
:traceflags (UCHAR): 32 system trace major code flags. Each bit corresponds to a trace major code,
hex 00-FFH. The most significant bit (left-most) of the first byte corresponds to major code hex 00H.
Value Definition 0 Trace disabled.

Trace enabled.

:maxtextsessions (UCHAR): Maximum number of VIO windowable sessions. :maxpmsessions (UCHAR):
Maximum number of Presentation Manager sessions.

;LocalSeg (PSEL) - output : Address of the selector for the local information segment structure, as
defined below: :processid (PID): Current process ID. :parentprocessid (PID): Parent process ID.
:threadpqty (USHORT): Priority of current thread. :threadid (TID): Current thread ID. :sessionid
(USHORT): Current session ID. :procstatus (UCHAR): Process status. :unused (UCHAR): Unused.
:foregroundprocess (BOOL): Current process is in foreground (has keyboard focus). Value -1 implies
yes, 0 implies no. :typeProcess (UCHAR): Type of process: Value Definition 0 Full screen protect mode
session. 1 Requires real mode. 2 VIO windowable protect mode session. 3 Presentation Manager
protect mode session. 4 Detached protect mode process. :unused (UCHAR): Unused. :environmentsel
(SEL): Environment selector. :cmdlineoff (USHORT): Command line offset in the segment addressed by
environmentsel. :dataseglen (USHORT): Length of data segment in bytes. :stacksize (USHORT): Stack
size in bytes. :heapsize (USHORT): Heap size in bytes. :hmodule (HMODULE): Module handle. :dssel
(SEL): Data segment selector.

Return Code

;rc (USHORT) - return:Return code description is: * 0 NO_ERROR

Remarks

Items of general interest are kept in the global information segment. Items of information specific to a particular process are kept in the local information segment. This information can be directly read by the application program. Both of these segments are defined as read-only segments. The application program cannot modify this data.

Assuming n1, n2, and n3 are the maximum number of full-screen sessions, VIO-windowable sessions, and Presentation Manager sessions, the first 0 through (n1-1) session numbers are assigned to full-screen sessions. The next n2 session numbers are assigned to VIO-windowable sessions, and the next n3 session numbers are assigned to Presentation Manager sessions. Session numbers in the range (n1+n2+n3) through 255 are reserved. Applications should use (n1+n2+n3-1) as an upper boundary. Applications should not assume that all session numbers starting with (n1+n2) and higher are Presentation Manager sessions.

The application program must be careful when referencing the date or time fields in the global information segment. A timer interrupt can be received by the system in between the instructions that read the individual fields, changing the data in these fields. For example, if the time is currently 23:59:59 on Tuesday, 6/2/87, the program can read the hours field (23). A timer interrupt can now be received, changing the time to 00:00:00 on Wednesday, 6/3/87. The program reads the rest of the time field (0 minutes) and the date field. The program would then think the current time and date is 23:00:00 on Wednesday, 6/3/87, which is incorrect.

The application program should read all time and date fields it uses as quickly as possible. It can then compare the least significant time field it uses (milliseconds, hundredths, seconds, or minutes) against the current value in the global information segment. If the value has not changed, the rest of the information is valid. If the value has changed, the program time or date information should be read again, as the information is updated while the program reads it.

Bindings

C

```
<PRE> typedef struct _GINFOSEG {
```

```
    ULONG    time;          /* time in seconds */
    ULONG    msecs;         /* milliseconds */
    UCHAR    hour;          /* hours */
    UCHAR    minutes;       /* minutes */
    UCHAR    seconds;       /* seconds */
    UCHAR    hundredths;    /* hundredths */
    USHORT   timezone;      /* minutes from UTC */
    USHORT   cusecTimerInterval; /* timer interval (units = 0.0001 seconds) */
    UCHAR    day;           /* day */
    UCHAR    month;         /* month */
    USHORT   year;          /* year */
```

```

UCHAR weekday;           /* day of week */
UCHAR uchMajorVersion;  /* major version number */
UCHAR uchMinorVersion;  /* minor version number */
UCHAR chRevisionLetter; /* revision letter */
UCHAR sgCurrent;        /* current foreground session */
UCHAR sgMax;            /* maximum number of sessions */
UCHAR cHugeShift;       /* shift count for huge elements */
UCHAR fProtectModeOnly; /* protect mode only indicator */
USHORT pidForeground;  /* pid of last process in foreground session */
UCHAR fDynamicSched;   /* dynamic variation flag */
UCHAR csecMaxWait;     /* max wait in seconds */
USHORT cmsecMinSlice;  /* minimum timeslice (milliseconds) */
USHORT cmsecMaxSlice;  /* maximum timeslice (milliseconds) */
USHORT bootdrive;      /* drive from which the system was booted */
UCHAR ameCRAS[32];     /* system trace major code flag bits */
UCHAR csgWindowableVioMax; /* maximum number of VIO windowable sessions */
UCHAR csgPMMax;         /* maximum number of pres. services sessions */

```

} GINFOSEG;

typedef struct _LINFOSEG {

```

PID    pidCurrent;        /* current process id */
PID    pidParent;         /* process id of parent */
USHORT prtyCurrent;     /* priority of current thread */
TID    tidCurrent;        /* thread ID of current thread */
USHORT sgCurrent;        /* session */
UCHAR  rfProcStatus;     /* process status */
UCHAR  dummy1;
BOOL   fForeground;       /* current process has keyboard focus */
UCHAR  typeProcess;      /* process type */
UCHAR  dummy2;
SEL    selEnvironment;   /* environment selector */
USHORT offCmdLine;       /* command line offset */
USHORT cbDataSegment;   /* length of data segment */
USHORT cbStack;          /* stack size */
USHORT cbHeap;           /* heap size */
HMODULE hmod;             /* module handle of the application */
SEL    selDS;              /* data segment handle of the application */

```

} LINFOSEG;

#define INCL_DOSINFOSEG

USHORT rc = DosGetInfoSeg(GlobalSeg, LocalSeg);

PSEL GlobalSeg; /* Address to place global segment (selector) */ PSEL LocalSeg; /* Address to place local segment (selector) */

USHORT rc; /* return code */ </PRE>

MASM

<PRE> GINFOSEG struc

gis_time	dd ? ;time in seconds
gis_msecs	dd ? ;milliseconds
gis_hour	db ? ;hours
gis_minutes	db ? ;minutes
gis_seconds	db ? ;seconds
gis_hundredths	db ? ;hundredths
gis_timezone	dw ? ;minutes from UTC
gis_cusecTimerInterval	dw ? ;timer interval (units = 0.0001 seconds)
gis_day	db ? ;day
gis_month	db ? ;month
gis_year	dw ? ;year
gis_weekday	db ? ;day of week
gis_uchMajorVersion	db ? ;major version number
gis_uchMinorVersion	db ? ;minor version number
gis_chRevisionLetter	db ? ;revision letter
gis_sgCurrent	db ? ;current foreground session
gis_sgMax	db ? ;maximum number of sessions
gis_cHugeShift	db ? ;shift count for huge elements
gis_fProtectModeOnly	db ? ;protect mode only indicator
gis_pidForeground	dw ? ;pid of last process in foreground session
gis_fDynamicSched	db ? ;dynamic variation flag
gis_csecMaxWait	db ? ;max wait in seconds
gis_cmsecMinSlice	dw ? ;minimum timeslice (milliseconds)
gis_cmsecMaxSlice	dw ? ;maximum timeslice (milliseconds)
gis_bootdrive	dw ? ;drive from which the system was booted
gis_amecRAS	db 32 dup (?) ;system trace major code flag bits
gis_csgWindowableVioMax	db ? ;maximum number of VIO windowable sessions
gis_csgPMMax	db ? ;maximum number of pres. services sessions

GINFOSEG ends

LINFOSEG struc

lis_pidCurrent	dw ? ;current process id
lis_pidParent	dw ? ;process id of parent
lis_prtCurrent	dw ? ;priority of current thread
lis_tidCurrent	dw ? ;thread ID of current thread
lis_sgCurrent	dw ? ;session
lis_rfProcStatus	db ? ;process status
lis_dummy1	db ? ;
lis_fForeground	dw ? ;current process has keyboard focus
lis_typeProcess	db ? ;process type
lis_dummy2	db ? ;
lis_selEnvironment	dw ? ;environment selector
lis_offCmdLine	dw ? ;command line offset
lis_cbDataSegment	dw ? ;length of data segment

```
lis_cbStack      dw  ? ;stack size
lis_cbHeap       dw  ? ;heap size
lis_hmod         dw  ? ;module handle of the application
lis_selDS        dw  ? ;data segment handle of the application
```

LINFOSEG ends

EXTRN DosGetInfoSeg:Far Incl_DosInfoSeg EQU 1

PUSH@ WORD GlobalSeg ;Global segment selector (returned) PUSH@ WORD LocalSeg ;Local segment selector (returned) CALL DosGetInfoSeg

Returns WORD </PRE>

From:
<http://osfree.su/doku/> - osFree wiki



Permanent link:

<http://osfree.su/doku/doku.php?id=en:docs:fapi:dosgetinfoseg&rev=1634394293>

Last update: **2021/10/16 14:24**