



This is part of **Family API** which allow to create dual-os version of program runs under OS/2 and DOS

Note: This is legacy API call. It is recommended to use 32-bit equivalent

2021/09/17 04:47 · prokushev · [0 Comments](#)

2021/08/20 03:18 · prokushev · [0 Comments](#)

This call loads a dynamic link module and returns a handle for the module.

Syntax

```
DosLoadModule (ObjNameBuf, ObjNameBufL, ModuleName, ModuleHandle)
```

Parameters

- ObjNameBuf (PSZ) - output: Address of the name of an object that contributed to the failure of DosLoadModule.
- ObjNameBufL (USHORT) - input: Length, in bytes, of the buffer described by ObjNameBuf.
- ModuleName (PSZ) - input: Address of the ASCIIZ name string containing the dynamic link module name or the pathname string. The filename extension used for dynamic link libraries is .DLL. When a pathname is provided, the module name may have any extension. The internal module name (the name given in the LIBRARY statement in the .DEF file) must be the same as the filename without the extension.
- ModuleHandle (PHMODULE) - output: Address of the handle for the dynamic link module.

Return Code

;rc (USHORT) - return:Return code descriptions are:

- 0 NO_ERROR
- 2 ERROR_FILE_NOT_FOUND
- 3 ERROR_PATH_NOT_FOUND
- 4 ERROR_TOO_MANY_OPEN_FILES
- 5 ERROR_ACCESS_DENIED
- 8 ERROR_NOT_ENOUGH_MEMORY
- 11 ERROR_BAD_FORMAT
- 26 ERROR_NOT_DOS_DISK
- 32 ERROR_SHARING_VIOLATION
- 33 ERROR_LOCK_VIOLATION
- 36 ERROR_SHARING_BUFFER_EXCEEDED
- 95 ERROR_INTERRUPT
- 108 ERROR_DRIVE_LOCKED
- 123 ERROR_INVALID_NAME
- 127 ERROR_PROC_NOT_FOUND
- 180 ERROR_INVALID_SEGMENT_NUMBER
- 182 ERROR_INVALID_ORDINAL

- 190 ERROR_INVALID_MODULETYPE
- 191 ERROR_INVALID_EXE_SIGNATURE
- 192 ERROR_EXE_MARKED_INVALID
- 194 ERROR_ITERATED_DATA_EXCEEDS_64k
- 195 ERROR_INVALID_MINALLOCSIZE
- 196 ERROR_DYNLINK_FROM_INVALID_RING
- 198 ERROR_INVALID_SEGDPL
- 199 ERROR_AUTODATASEG_EXCEEDS_64k
- 201 ERROR_RELOC_CHAIN_XEEDS_SEGLIM
- 206 ERROR_FILENAME_EXCED_RANGE

Remarks

If the file is an OS/2 dynamic link module, it is loaded, and a handle is returned. This handle is used for freeing the dynamic link module with a [DosFreeModule](#) request, getting procedure addresses with [DosGetProcAddr](#) requests, and getting the fully qualified file name with a [DosGetModName](#) request.

DosLoadModule may not be called from a dynamic library initialization routine if the module to be loaded or any module referenced by it contains a dynamic link library initialization routing.

Bindings

C

```
#define INCL_DOSMODULEMGR

USHORT rc = DosLoadModule(ObjNameBuf, ObjNameBufL, ModuleName,
ModuleHandle);

PSZ      ObjNameBuf;      /* Address of object name buffer */
USHORT   ObjNameBufL;    /* Length of object name buffer */
PSZ      ModuleName;     /* Address of module name string */
PHMODULE ModuleHandle;   /* Address of module handle (returned) */

USHORT   rc;              /* return code */
```

MASM

```
EXTRN DosLoadModule:FAR
INCL_DOSMODULEMGR EQU 1

PUSH@   OTHER   ObjNameBuf      ;Object name buffer (returned)
PUSH    WORD    ObjNameBufL     ;Length of object name buffer
PUSH@   ASCIIZ  ModuleName      ;Module name string
PUSH@   WORD    ModuleHandle    ;Module handle (returned)
CALL    DosLoadModule
```

Returns **WORD**

Example

This example loads a module.

```
#define INCL_DOSMODULEMGR

#define MODULE_NAME "abcd"
#define FULL_MODULE_NAME "\\nifty\\abcd.dll"

CHAR    LoadError[100];
HMODULE ModuleHandle;
USHORT  rc;

    if (DosLoadModule(LoadError,          /* Object name buffer */
                    sizeof(LoadError),   /* Length of object name buffer */
                    MODULE_NAME,        /* Module name string */
                    &ModuleHandle) == 2) /* Module handle */
```

Family API

| | | |
|---------|---|--|
| DOS | Process Manager | DosBeep DosExit DosSleep DosExecPgm |
| | File Manager | DosChDir DosChgFilePtr DosClose DosDelete DosDupHandle DosMkDir DosMove DosQCurDir DosQCurDisk DosSetFileMode DosOpen DosQFileInfo DosRead DosQFileMode DosQFSInfo DosQVerify DosRmDir DosSelectDisk DosFindClose DosFindFirst DosFindNext DosSetFileInfo DosSetVerify DosWrite DosFileLocks DosSetFHandState DosNewSize DosBufReset DosQFHandState DosSetFSInfo DosShutdown |
| | Memory Manager | DosFreeSeg DosSubAlloc DosSubFree DosSubSet DosAllocHuge DosAllocSeg DosReallocHuge DosReallocSeg DosGetHugeShift DosCreateCSAlias |
| | NLS | DosCaseMap DosGetCtryInfo DosGetDBCSEv DosSetCtryCode DosGetCollate DosGetMessage DosInsMessage DosPutMessage |
| | Date and Time | DosSetDateTime DosGetDateTime |
| | Devices | DosDevConfig DosDevIOct1 DosDevIOct2 |
| | Signals | DosHoldSignal DosSetSigHandler |
| | Misc | BadDynLink DosGetEnv DosGetMachineMode DosGetVersion DosError DosErrClass DosSetVec |
| KBD | KbdCharIn KbdFlushBuffer KbdGetStatus KbdSetStatus KbdStringIn KbdPeek | |
| VIO | VioGetBuf VioGetConfig VioGetCurPos VioGetCurType VioGetPhysBuf VioReadCellStr VioReadCharStr VioScrollUp VioScrollDn VioScrollLf VioScrollRt VioScrUnLock VioSetCurPos VioSetCurType VioSetMode VioGetMode VioShowBuf VioWrtCellStr VioWrtCharStr VioWrtCharStrAtt VioWrtNAttr VioWrtNCell VioWrtNChar VioWrtTTY VioScrLock VioPopUp | |
| Tools | BIND | |
| Modules | DOSCALLS.DLL VIOCALLS.DLL KBDCALLS.DLL MSG.DLL | |

Family API

Libraries [API.LIB](#) [OS2386.LIB](#) [FAPI.LIB](#) [DOSCALLS.LIB](#) [SUBCALLS.LIB](#)

2018/08/25 15:05 · prokushev · [0 Comments](#)

From:

<http://osfree.su/doku/> - **osFree wiki**

Permanent link:

<http://osfree.su/doku/doku.php?id=en:docs:fapi:dosloadmodule&rev=1631326709>

Last update: **2021/09/11 02:18**

