

## MouFlushQue

**Bindings:** C, MASM

This call directs the mouse driver to flush (empty) the mouse event queue and the monitor chain data for the session.

*MouFlushQue* (**DeviceHandle**)

*DeviceHandle* (**HMOU**) - input Mouse device handle from a previous [MouOpen](#).

*rc* (**USHORT**) - return Return code descriptions are:

<b>0</b>	<b>NO_ERROR</b>
385	ERROR_MOUSE_NO_DEVICE
466	ERROR_MOU_DETACHED
501	ERROR_MOUSE_NO_CONSOLE
505	ERROR_MOU_EXTENDED_SG

### C bindings

```
#define INCL_MOUSE

USHORT rc = MouFlushQue(DeviceHandle);

HMOU DeviceHandle; /* Mouse device handle */

USHORT rc; /* return code */
```

### MASM bindings

```
EXTRN MouFlushQue:FAR
INCL_MOUSE EQU 1

PUSH WORD DeviceHandle ;Mouse device handle
CALL MouFlushQue

Returns WORD
```

From:  
<http://osfree.su/doku/> - **osFree** wiki

Permanent link:  
<http://osfree.su/doku/doku.php?id=en:ibm:prcp:mou:flushque>

Last update: **2016/09/15 03:38**

