



Note: This API calls are shared between DOS and Win16 personality.

DPMI is a shared interface for DOS applications to access Intel 80286+ CPUs services. DOS DMPI host provides core services for protected mode applications. Multitasking OS with DOS support also provides DMPI in most cases. Windows standard and extended mode kernel is a DPMI client app. Standard and extended mode kernel differs minimally and shares common codebase. Standard Windows kernel works under DOSX extender. DOSX is a specialized version of 16-bit DPMI Extender (but it is standard DPMI host). Standard mode is just DPMI client, enhanced mode is DPMI client running under Virtual Machine Manager (really, multitasker which allow to run many DOS sessions). Both modes shares DPMI interface for kernel communication. The OS/2 virtual DOS Protected Mode Interface (VDPMI) device driver provides Version 0.9 DPMI support for virtual DOS machines. Win16 (up to Windows ME) provides Version 0.9 DPMI support. Windows in Standard Mode provides DPMI services only for Windows Applications, not DOS sessions.

DPMI host often merged with DPMI extender. Usually DPMI extender provide DPMI host standard services and DOS translation or True DPMI services.

2021/08/05 10:15 · prokushev · [0 Comments](#)

Int 31H, AH=00H, AL=0DH

Version

0.9

Brief

Allocate Specific LDT Descriptor

Input

```
AX = 000DH  
BX = selector
```

Return

```
if function successful  
Carry flag = clear  
and descriptor has been allocated
```

```
if function unsuccessful
Carry flag = set
AX = error code
8011H  descriptor unavailable (descriptor is in use)
8022H  invalid selector (references GDT or beyond the LDT limit)
```

Notes

The first 10H (16) descriptors (selector values 04H-7CH) are reserved for this function and must not be used by the DPMI host.

Under DPMI 0.9 hosts, if another application has already been loaded, some of descriptors reserved for allocation by this function may be already in use and unavailable. Under DPMI 1.0 hosts, each client has its own LDT and thus will have the full 16 descriptors available for use with this function.

Resident service providers (protected-mode TSRs) should not use this function.

Refer to the rules for descriptor usage in Appendix D.

See also

Note

Text based on <http://www.delorie.com/djgpp/doc/dpmi/>

DPMI	
Process manager	INT 2FH 1680H, 1687H
Signals	
Memory manager	
Misc	INT 2FH 1686H, 168AH
Devices	

2021/08/13 14:23 · prokushev · 0 Comments

From:
<https://www.osfree.org/doku/> - **osFree wiki**

Permanent link:
<https://www.osfree.org/doku/doku.php?id=en:docs:dpmi:api:int31:00:0d>

Last update: **2021/08/27 01:50**

