

This call allows a process to query the code page being used to translate scan codes to ASCII characters.

Syntax

KbdGetCp (Reserved, CodePageID, KbdHandle)

Parameters

;Reserved (ULONG) - input: Reserved and must be set to zero. ;CodePageID (USHORT) - output: Address of the code page ID located in the application's data area. The keyboard support copies the current code page ID for a specified keyboard handle into this word. The code page ID is equivalent to one of the code page IDs specified in the CONFIG.SYS CODEPAGE = statement or 0000. ;KbdHandle (HKBD) - input: Default keyboard or the logical keyboard.

Return Code

;rc (USHORT) - return:Return code descriptions are: ::0 NO_ERROR ::373 ERROR_KBD_PARAMETER
::439 ERROR_KBD_INVALID_HANDLE ::445 ERROR_KBD_FOCUS_REQUIRED ::447
ERROR_KBD_KEYBOARD_BUSY ::464 ERROR_KBD_DETACHED ::504 ERROR_KBD_EXTENDED_SG

Remarks

The CodePageID is the currently active keyboard code page. A value of 0 indicates the code page translation table in use is the ROM code page translation table provided by the hardware.

Bindings

C

```
<PRE> #define INCL_KBD
```

```
USHORT rc = KbdGetCp(Reserved, CodePageID, KbdHandle);
```

```
ULONG Reserved; /* Reserved (must be zero) */ PUSHORT CodePageID; /* Code Page ID */ HKBD  
KbdHandle; /* Keyboard handle */
```

```
USHORT rc; /* return code */ </PRE>
```

MASM

```
<PRE> EXTRN KbdGetCp:FAR INCL_KBD EQU 1
```

PUSH DWORD Reserved ;Reserved (must be zero) PUSH@ WORD CodePageID ;Code Page ID PUSH
WORD KbdHandle ;Keyboard handle CALL KbdGetCp

Returns WORD </PRE>

[Kbd](#)

From:

<https://osfree.su/doku/> - **osFree wiki**

Permanent link:

<https://osfree.su/doku/doku.php?id=en:docs:fapi:kbdgetcp&rev=1633521635>

Last update: **2021/10/06 12:00**

