



This is part of **Family API** which allow to create dual-os version of program runs under OS/2 and DOS

**Note:** This is legacy API call. It is recommended to use 32-bit equivalent

2021/09/17 04:47 · prokushev · [0 Comments](#)

2021/08/20 03:18 · prokushev · [0 Comments](#)

## MouClose

MouClose closes the mouse device for the current session and removes the mouse device driver handle from the list of valid open mouse device handles.

### Syntax

```
MouClose (DeviceHandle)
```

### Parameters

- DeviceHandle (HMOU) - input : Mouse device handle from a previous MouOpen.

### Return Code

rc (USHORT) - return:Return code descriptions are:

- 0 - NO\_ERROR
- 385 - ERROR\_MOUSE\_NO\_DEVICE
- 466 - ERROR\_MOU\_DETACHED
- 501 - ERROR\_MOUSE\_NO\_CONSOLE
- 505 - ERROR\_MOU\_EXTENDED\_SG

### Bindings

#### C

```
#define INCL_MOU

USHORT rc = MouClose(DeviceHandle);

HMOU DeviceHandle; /* Mouse device handle */
```

```
USHORT rc; /* return code */
```

## MASM

```
EXTRN MouClose:FAR
INCL_MOU EQU 1

PUSH WORD DeviceHandle ;Mouse device handle
CALL MouClose

Returns WORD
```

From:

<https://osfree.su/doku/> - osFree wiki

Permanent link:

<https://osfree.su/doku/doku.php?id=en:docs:fapi:mouclose&rev=1634264884>

Last update: **2021/10/15 02:28**

