

KbdGetHWId

Bindings:

C:

```
typedef struct _KBDHWID {
    USHORT length;           /* length in bytes of this structure */
    USHORT kbd_id;          /* attached keyboard's hardware ID
                           (returned) */
    USHORT reserved1;       /* reserved (set to zero) */
    USHORT reserved2;       /* reserved (set to zero) */
}KBDHWID;

#define INCL_KBD

USHORT rc = KbdGetHWId(KeyboardID, KbdHandle);

PKBDHWID      KeyboardID;   /* Keyboard ID structure (returned) */
HKBD          KbdHandle;    /* Keyboard handle */

USHORT        rc;           /* return code */
```

MASM:

```
KBDHWID struc
    length;                dw ? ;length in bytes of this structure
    kbd_id;                dw ? ;attached keyboard's hardware ID (returned)
    reserved1;            dw ? ;reserved (set to zero)
    reserved2;            dw ? ;reserved (set to zero)
KBDHWID ends

EXTRN KbdGetHWId:FAR
INCL_KBD EQU 1

PUSH@ OTHER KeyboardID    ;Keyboard ID structure (returned)
PUSH WORD KbdHandle       ;Keyboard handle
CALL KbdGetHWId

Returns WORD
```

Returns the attached keyboard's hardware-generated Identification value.

KbdGetHWId (KeyboardID, KbdHandle)

KeyboardID (**PKBDHWID**) - input Pointer to the caller's data area where the following structure and data values are:

length (**USHORT**) - input/output On input, this field should contain the length of the *KeyboardID* structure. The minimum input length value allowed is 2. On output, this field contains the actual number of bytes returned.

keybdid (**USHORT**) - output OS/2 supported keyboards and their hardware generated IDs are as follows:

| ID | Keyboard |
|-------|----------------------------------|
| 0000H | Undetermined keyboard type |
| 0001H | PC-AT Standard Keyboard |
| AB41H | 101 Key Enhanced Keyboard |
| AB41H | 102 Key Enhanced Keyboard |
| AB54H | 88 and 89 Key Enhanced Keyboards |
| AB85H | 122 Key Enhanced Keyboard |

reserved (**USHORT**) Reserved and returned set to zero.

reserved (**USHORT**) Reserved and returned set to zero.

KbdHandle (**HKBD**) - input Word identifying the logical keyboard.

rc (**USHORT**) - return Return code descriptions are:

| | |
|-----|-------------------------|
| 0 | NO_ERROR |
| 373 | ERROR_KBD_PARAMETER |
| 447 | ERROR_KBD_KEYBOARD_BUSY |
| 464 | ERROR_KBD_DETACHED |
| 504 | ERROR_KBD_EXTENDED_SG |

Remarks

In past OS/2 releases, all keyboards could be supported by knowing the hardware family information available with keyboard IOCTL 77H. However, with the addition of the 122-key keyboard, recognition was not containable by hardware family information alone. The 122-key keyboard has a number of differences from other keyboards. Therefore, applications performing keystroke specific functions may need to determine specifically which keyboard is attached.

This function is of particular usefulness for applications providing Custom Translate Tables and mapping keyboard layouts.

From:

<https://osfree.su/doku/> - **osFree wiki**

Permanent link:

<https://osfree.su/doku/doku.php?id=en:ibm:prcp:kbd:gethwid&rev=1400260642>

Last update: **2014/05/16 17:17**

