# VioEndPopup

**Bindings**: C, MASM

This call is issued by the application when it no longer requires the temporary screen obtained through a previous VioPopUp call.

*VioEndPopUp* (VioHandle)

*VioHandle* (**HVIO**) - input A reserved word of 0s.

*rc* (**USHORT**) - return Return code descriptions are:

| | |
|---|---|
| 0 | NO_ERROR |
| 405 | ERROR_VIO_NO_POPUP |
| 436 | ERROR_VIO_INVALID_HANDLE |

### Remarks

When the application issues a VioEndPopUp call, all video calls are directed to the application's normal video buffer.

### PM Considerations

An error is returned if issued with a non-zero handle.

### C bindings

```
#define INCL_VIO

USHORT  rc = VioEndPopUp(VioHandle);

HVIO             VioHandle;     /* Vio device handle */

USHORT           rc;            /* return code */
```

### MASM bindings

```
EXTRN  VioEndPopUp:FAR
INCL_VIO            EQU 1

PUSH   WORD    VioHandle     ;Vio device handle
CALL   VioEndPopUp

Returns WORD
```

From:
https://osfree.su/doku/ - **osFree wiki**

Permanent link:
**https://osfree.su/doku/doku.php?id=en:ibm:prcp:vio:endpopup**

Last update: **2016/09/14 10:49**